

Specifications

				KUBOTA	
Model		Z411KW-48-AU		Z421KW-54-AU	
Engine	Model	GH7302V		GH7301V	
	Type	Air cooled 2 cylinders petrol engine			
	Engine Gross power	HP	22.0		24.0
	Total displacement	cu.in. (cc)	44.3 (726)		
	Starting system	Key switch			
Dimensions	Overall length	mm	2055		
	Overall width	w/ mower	mm	1552	1710
		w/ RCPS (upright)	mm	1236	1772
	Overall height	mm	1266		
		mm	1255		
Wheelbase			1000		
Tread/Tyre	Tread	Front	mm	944	
		Rear	mm	1000	
	Tyre size	Front tyre	mm	13 x 5.0 - 6, Smooth pneumatic	
		Rear tyre	mm	24 x 9.5 - 14, Low profile tyre	
Weight (w/ mower)			kg	394	400
Transmission	Hydro-Gear® Commercial ZT3600®				
Transmission system	2-HST w/Gear reduction				
Speed control	2-hand lever				
Travelling speed range	Forward	km/h	0 - 16.0		
	Reverse	km/h	0 - 8.0		
Braking system	Cog style parking lock / Foot pedal				
PTO	Type	Belt drive			
	Clutch type	Electric clutch			
	PTO brake	Dry disc			
Mower deck	Model	RCK48P-400Z		RCK54P-400Z	
	Mower deck type	Side discharge			
	Mower lift system	Mechanical / Foot pedal			
	Deck depth	in. (mm)	5.0 (127)		
	Belt type	Belt drive			
	Deck steel thickness	in. (mm)	0.135 (3.4)		
	Anti scalp roller	Rigid			
	Cutting width of mower	in. (mm)	40 (1019)		54 (1372)
	Number of blades	5			
	Cutting height	in. (mm)	1.5 - 5.0 (38 - 127)		
	Mounting system of mower	Parallel linkage			
Blade tip speed	FPM (m/s)	16900 (95.0)		16700 (95.0)	
Seat	Suspension seat				
Engine stop system	Key stop				
Fuel tank capacity			25.7		
Battery	U1 (12V, RC : 45min, CCA : 300, CA : 410)				
Generator capacity	Amp		15A		
Hour meter	Standard				
Fuel gauge	Sight window				

These Kawasaki engines have been tested in accordance with SAE J1995, verified by TÜV Rheinland Group, and certified by SAE International. The gross power ratings of these engines were determined by using measurements according to SAE J1995 which were witnessed by SAE-approved witnesses from TÜV Rheinland Group. Torque ratings of these engines were not certified by SAE. Actual power and torque output will vary depending on numerous factors, including, but not limited to, the operating speed of the engine in application, environmental conditions, maintenance, and other variables.

**Power (hp) specifications for individual gasoline engine models are rated pursuant to Society of Automotive Engineers (SAE) J1940 or J2723 based on gross output testing performed in accordance with SAE J1995 without the air cleaner and muffler. Gross engine hp will be higher than actual engine power which is affected by accessories, application, engine speed, ambient operating conditions and other factors. The gross engine horsepower information is for comparison purposes only.

The company reserves the right to change the above specifications without notice.

This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information.

For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (RCPS) and seat belt in almost all applications.

Attachment & Option Kit



- **Grass Catcher**
The optional 7 bushels (250 liters) grass catcher can be attached and detached without ever requiring the use of any tools.



- **Mulching Kit**
- **LED Work Lights**
- **OCDC**
- **Maintenance Lift Kit**

©2017 Kubota Corporation

Kubota

KUBOTA Tractor Australia Pty Ltd

25-29 Permas Way, TRUGANINA Vic, 3029

Freecall: 1800-334-653

Email: sales@kubota.com.au

Web Site: <http://www.kubota.com.au>

CB Norwood Distributors Ltd

PO Box 1265, 888 Tiemaine Avenue,

Palmerston North 0800 KUBOTA

Tel: 06 356 4920 Fax: 06 356 4939

Web Site: <http://www.kubota.co.nz>