



Rear Blades

Put your gardening, landscaping, driveway, and ditch-maintenance chores behind you with a sturdy Rear Blade.

- Easy adjustment simplifies grading and leveling
- iMatch™ or Quick-Coupler compatible



Box Blades

Frontier Box Blades level uneven ground and simplify grading tasks.

- Tailgate can be fixed or float
- Shanks are easily replaceable
- iMatch and/or Quick-Coupler compatible

Model	Duty / Working Width	PTO HP ²	Hitch
RB5048L	Economy / 48 in. (121.9 cm)	18 hp (13.4 kW) maximum	Ltd. Cat. 1
RB5060L	Economy / 60 in. (152.4 cm)	18 hp (13.4 kW) maximum	Ltd. Cat. 1
RB2060L	Economy / 60 in. (152.4 cm)	25 hp (18.6 kW) maximum	Ltd. Cat. 1
RB2060	Standard / 60 in. (152.4 cm)	19 - 45 hp (14.1 - 33.6 kW)	Cat. 1
RB5060	Standard / 60 in. (152.4 cm)	20 - 56 hp (14.9 - 41.8 kW)	Cat. 1
RB2160 ²	Medium / 60 in. (152.4 cm)	65 hp (48.5 kW) maximum	Cat. 1
RB2160H ²	Standard Plus / 60 in. (152.4 cm)	50 hp (37.3 kW) maximum	Cat. 1
RB2072	Standard / 72 in. (182.9 cm)	23 - 55 hp (17.1 - 41.0 kW)	Cat. 1
RB5072	Standard / 72 in. (182.9 cm)	20 - 56 hp (14.9 - 41.8 kW)	Cat. 1
RB2172 ²	Medium / 72 in. (182.9 cm)	65 hp (48.5 kW) maximum	Cat. 1
RB2172H ²	Standard Plus / 72 in. (182.9 cm)	65 hp (48.5 kW) maximum	Cat. 1
RB2272 ²	Medium Plus / 72 in. (182.9 cm)	80 hp (59.6 kW) maximum	Cat. 2
RB2084	Standard / 84 in. (213.4 cm)	27 - 55 hp (20.1 - 41.0 kW)	Cat. 1
RB5084	Standard / 84 in. (213.4 cm)	20 - 56 hp (14.9 - 41.8 kW)	Cat. 1
RB2184 ²	Medium / 84 in. (213.4 cm)	65 hp (48.5 kW) maximum	Cat. 1
RB2184H ²	Standard Plus / 84 in. (213.4 cm)	50 hp (37.3 kW) maximum	Cat. 1
RB2284 ²	Medium Plus / 84 in. (213.4 cm)	80 hp (59.6 kW) maximum	Cat. 2
RB2307 ^{1,2}	Heavy / 84 in. (213.4 cm)	120 hp (89.5 kW) maximum	Cat. 2
RB5096	Standard / 96 in. (243.8 cm)	20 - 56 hp (14.9 - 41.8 kW)	Cat. 1
RB2308 ^{1,2}	Heavy / 96 in. (243.8 cm)	120 hp (89.5 kW) maximum	Cat. 2
RB2196 ²	Medium / 96 in. (243.8 cm)	65 hp (48.5 kW) maximum	Cat. 1
RB2196H ²	Standard Plus / 96 in. (243.8 cm)	50 hp (37.3 kW) maximum	Cat. 1
RB2296 ²	Medium Plus / 96 in. (243.8 cm)	80 hp (59.7 kW) maximum	Cat. 2
RB2408 ^{1,2}	Heavy Plus / 96 in. (243.8 cm)	160 hp (119.3 kW) maximum	Cat. 2 and 3
RB2309 ^{1,2}	Heavy / 108 in. (274.3 cm)	120 hp (89.5 kW) maximum	Cat. 2
RB2409 ^{1,2}	Heavy Plus / 108 in. (274.3 cm)	160 hp (119.3 kW) maximum	Cat. 2 and 3
RB2310 ^{1,2}	Heavy / 120 in. (304.8 cm)	120 hp (89.5 kW) maximum	Cat. 2
RB2410 ^{1,2}	Heavy Plus / 120 in. (304.8 cm)	160 hp (119.3 kW) maximum	Cat. 2 and 3

¹Hydraulic tilt, angle, and offset function available ²Reduce the hp requirement by 5 hp if the tractor has MFWD

Model	Working Width	PTO HP	Hitch
BB2048L	48 in. (121.9 cm)	25 hp (18.6 kW) maximum	Cat. 0 / Ltd. Cat. 1
BB2048	48 in. (121.9 cm)	45 hp (33.5 kW) maximum	Cat. 1
BB5048L	48 in. (121.9 cm)	18 hp (13.4 kW) maximum	Ltd. Cat. 1
BB2060	60 in. (152.4 cm)	55 hp (41 kW) maximum	Cat. 1
BB5060L	60 in. (152.4 cm)	18 hp (13.4 kW) maximum	Ltd. Cat. 1
BB5060	61.5 in. (156.2 cm)	17 - 56 hp (12.8 - 41.8 kW) maximum	Cat. 1
BB2065	66 in. (167.6 cm)	55 hp (41.0 kW) maximum	Cat. 1
BB2072	72 in. (182.9 cm)	55 hp (41.0 kW) maximum	Cat. 1
BB2172	72 in. (182.9 cm)	70 hp (52.2 kW) maximum	Cat. 1
BB3272	72 in. (182.9 cm)	80 hp (59.6 kW) maximum	Cat. 1 and 2
BB5072	73.5 in. (186.7 cm)	56 hp (41.8 kW) maximum	Cat. 1
BB2184	84 in. (213.4 cm)	70 hp (52.2 kW) maximum	Cat. 1
BB3284	84 in. (213.4 cm)	80 hp (59.6 kW) maximum	Cat. 1 and 2
BB5084	85.5 in. (217.2 cm)	56 hp (41.8 kW) maximum	Cat. 1
BB3296	96 in. (243.8 cm)	80 hp (59.6 kW) maximum	Cat. 1 and 2
BB5096	97.5 in. (247.7 cm)	56 hp (41.8 kW) maximum	Cat. 1