

	3032E	3038E	3033R	3039R	3046R
ENGINE					
Type	Yanmar 3TNV88C	Yanmar 3TNV86T	Yanmar 3TNV88C	Yanmar 3TNV86CT	Yanmar 3TNV86CHT
Horsepower †	31.1 (28.1 kw) †	37.7 (28.1 kw) †	32.2 (23.7 kw)	38.7 (28.5 kw)	45.3 (33.3 kw)
PTO HP Geared Transmission	—	—	24.8 (18.5 kw)	31.6 (23.6 kw)	—
PTO HP Hydrostatic Transmission	25.0 (18.6 kW)	30.0 (22.4 kW)	24.3 (18.1 kw)	31.1 (23.2 kw)	34.1 (27.3 kw)
Rated Speed, rpm	2,500	2,500	2,600	2,600	2,600
Engine Displacement	100.2 cu. in. (1.64 L)	95.7 cu. in. (1.57 L)	100.2 cu. in. (1.64 L)	95.7 cu. in. (1.57 L)	95.7 cu. in. (1.57 L)
Battery Power	12V, 500 CCA	12V, 500 CCA	12V, 500 CCA	12V, 500 CCA	12V, 500 CCA
Alternator	75 A	75 A	75 A	75 A	75 A
HYDRAULICS					
Steering	4.0 gpm (15.0 L/min)	4.0 gpm (15.0 L/min)	5.3 gpm (20 L/min)	5.3 gpm (20 L/min)	5.3 gpm (20 L/min)
Implement	5.3 gpm (20.2 L/min)	5.3 gpm (20.2 L/min)	8.6 gpm (32.5 L/min)	8.6 gpm (32.5 L/min)	8.6 gpm (32.5 L/min)
Total capacity	9.3 gpm (35.2 L/min)	9.3 gpm (35.2 L/min)	13.9 gpm (52.5 L/min)	13.9 gpm (52.5 L/min)	13.9 gpm (52.5 L/min)
Lift capacity (24 in. behind center link)	1,356 lb. (615 kg)	1,356 lb. (615 kg)	2,200 lb. (999 kg)	2,200 lb. (999 kg)	2,200 lb. (999 kg)
TRANSMISSION					
Standard	Hydrostatic – 2 Range	Hydrostatic – 2 Range	PowrReverser 12F/12R	PowrReverser 12F/12R	eHydro
Optional	NA	NA	Hydrostatic – 3 Range	Hydrostatic – 3 Range	NA
Final drive	Spur Gear	Spur Gear	Helical Gear	Helical Gear	Helical Gear
Brakes	Wet Disk	Wet Disk	Wet Disk	Wet Disk	N/A
Steering	Power	Power	Power	Power	Power
PTO					
PTO type	Independent	Independent	Independent	Independent	Independent
PTO	Rear 540	Rear 540	Rear 540	Rear 540	Rear 540
PTO Options	—	—	Mid	Mid	Mid
REAR HITCH					
Type	Category 1	Category 1	Category 1	Category 1	Category 1
Control type	Position	Position	Position	Position	Position
WEIGHT					
Open Station 4WD/MFWD	2,222 lb. (1008 kg)	2,222 lb. (1008 kg)	2,900 lb. (1316 kg)	2,900 lb. (1316 kg)	2,900 lb. (1316 kg)
Cab MFWD			3,570 lb. (1619 kg)	3,570 lb. (1619 kg)	3,570 lb. (1619 kg)
LOADER					
Max Height Lift Capacity at Pivot**	1,186 lb. (539 kg)	1,186 lb. (539 kg)	1,598 lb. (725 kg)	1,598 lb. (725 kg)	1,598 lb. (725 kg)

† Rated engine horsepower (ISO) per SAE J1995

** For a complete list of loader specifications see your dealer.

‡ The engine horsepower and torque information are provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower and torque will be less. Refer to the manufacturer's web site for additional information.